





TWO-way ball valve, “Integral Seal” Three Pieces, revolving round sleeves
Drive: ISO 5211 – DIN 3337 flange for actuator
Drive: Inox lever
Connection: Butt-welding in according to BS-OD (ASTM A-270)
Flow: Full
Material: Aisi 316L (1.4404)
Measure: from DN10 to DN100
Seals: Virgin P.T.F.E.
Operating temperature: -20°C+160°C
Outer finish: Polished
Screws for mounting actuator included

On request:
Antistatic device ATEX:
II 2G Ex h IIC T4 Gb
II 2D Ex h IIIC T135°C Db
M.O.C.A. CE 1935/2004


Øa
Øc +0,1 +0,2
d
o
b
H
B
ØA
DN
Ø
M
L
f n°4 fori
45°
45°
e


13
10
8
9
5
7
12
4
3
6
2
1
6
3
4
11


Diagramma Pressione/Temperatura
Ptfe Vergine -20°,+160°C
bar
0
10
20
30
40
50
60
70
-20
0
20
40
60
80
100
120
140
160
180
200
220
° C


Pressure / Temperature Diagram
Ptfe Virgin -4°,+320°F
psi
0
100
200
300
400
500
600
700
800
900
1000
-4
16
36
56
76
96
116
136
156
176
196
216
236
256
276
296
316
336
° F